

## 24 FIBRE OPTICAL FIBRE ENCLOSURE MEDIUM

This IP65 lockable enclosure offers the ability to terminate 24 fibres housed in a strong, robust, ABS enclosure for indoor and outdoor applications. The enclosure can accept a number of adaptor types, with two incoming cable entry points and 12 patch cord exit points that are sealed to ensure the IP65 rating is protected once installed. There are integrated cable tie positions and fibre bend radius protection. Both the front lockable door and splice tray are detachable to enable easy installation.

### FEATURES

- Supports up to IP65
- Supports up to 24 fibres
- 12 adaptor positions
- Hinged/detachable splice tray assists installation
- Multiple adaptor options available
- Secure lockable front door
- Supplied with heat shrink splice protectors, fibre transit tubing, wall fixings and cable ties
- Integrated bend radius protection
- Detachable door for ease of installation
- ROHS, REACH & SvHC materials compliant



### TECHNICAL SPECIFICATION

Height - Width - Depth	235mm x 205mm x 60mm
Net weight	0.9kg
Material	ABS
Suitable for adaptor types	SC Simplex, LC Duplex
Cable Entry	2
Cable Exit	12 Patch Cords
IP Rating	IP65
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754



Part Number: **FE-IP65-12-SC-SPX-MED-HINGE**