

16 FIBRE OPTICAL FIBRE ENCLOSURE WITH LID

This IP65 lockable enclosure offers the ability to terminate 16 fibres housed in a strong, robust, ABS enclosure for indoor and outdoor applications. The enclosure can accept multiple adaptor types, with one incoming and two outgoing cable glands, that are sealed to ensure the IP65 rating is maintained once installed. The enclosure has a detachable front door and hinged/detachable splice tray that allows for easy access during installation or re-work. There are also integrated cable tie positions and fibre bend radius protection.

FEATURES

- IP65 rated
- Supports up to 16 fibres
- Hinged/removable splice tray assists installation
- 8 adaptor positions
- Multiple adaptor options available
- Removable front cover for easy installation
- Supplied with heat shrink splice protectors, transit tubing, wall fixings and cable ties
- Integrated bend radius protection
- 2 Sealing glands for exiting cables and 1 entry cable
- ROHS, REACH & SvHC materials compliant



TECHNICAL SPECIFICATION

Height - Width - Depth	210mm x 175mm x 50mm
Net weight	0.44kg
Material	ABS
Suitable for adaptor type	SC Simplex, LC Duplex
Cable Entry	1
Cable Exit	2
IP Rating	IP65
Designed in accordance with	TIA/EIA 568.C, EN50173, IEC60304, IEC61754, EN297-1, ISO/IEC 11801



Part Number: **FE-IP65-8-SC-SPX-MED-LID**