

FIBRE OPTIC SPLICE ENCLOSURE - 48 FIBRES

The Fiber Optic Splice Closure is constructed from premium-grade ABS material. Specifically designed to provide a versatile solution for splicing and branching off fibre optic cables across diverse environments, the Mini Fiber Optic Splice Enclosure ensures reliability. The enclosure features a silicone sealing gasket positioned between the cover and base, enhancing its protective capabilities. It is suitable for deployment on-site with various cable types and splicing tools.

FEATURES

- IP65 rated
- Robust ABS construction
- Supports up to 48 fibres (4 x 12 way splice trays)
- Compact design
- Ideal to install in restricted areas
- 4 Ports - 2 x Entry / 2 x Exit
- Silicone sealing gasket

APPLICATIONS

- CATV networks
- Optical fibre communication
- FTTH
- FTTH access network
- Telecommunication networks
- Data communications networks
- LAN
- Wall mounting



TECHNICAL SPECIFICATIONS

IP Rating	IP65
Dimensions (mm) (LxWxH)	230 x 185 x 85
Life Cycle	185
Max. Capacity	48 fibre cores / 4 x 12
Cable ports	4 - 2 x entry / 2 x exit
Cable Diameter (mm)	2 ~ 9
Material	PP
Installation	Wall mount
Environmental Temperature (°C)	-40°c to +65°c
Voltage Resistance	15kv/DC/1min
Insulation Resistance	≥2X104MΩ